Locking Door Pull How to Order

Product Category	Locking vs. Non-locking	Function	Locking Position	Turn Style	Panel Thickness (mm)	CTC/OAL	Finish	Keying System	Strike
LDP	1	A	1	1	A	925/1200	630	A	0
LDP (Round Tube)	1 = Locking	A = Cylinder x Turn	1 = Bottom Only	1 = Standard Turn	A = 10 – 12.9	925/1200	630	A = Standard key cylinder	1 = Standard bottom
LDPQ (Square tube)	2= Non-locking	B = Cylinder Only	2 = Top Only	2 = ADA Turn	B = 13.0 – ?	(Specify)	629	B = SFIC	2 = Bottom with Flange
		C = Turn only	3 = Top and Bottom	0 = Non-Locking	C = 45mm		(Specify)	0 = Non-Locking	3 = Shallow Bottom
		D = No Inside Grip	4 = Side Locking (on glass)	3 = Locking with no turn	D = 80mm			C = Euro Profile	4 = Top locking BTB
		N = Non-Locking	0 = Non-Locking		E = ½” w/special square shaped end			D = Schlage LFIC	5 = Top locking Single Side
					F = 8 - 10			E = Sargent LFIC	0 = N/A
								F = Medeco LFIC	
								G = Yale LFIC	
								H = Salto XS4 Geo	